




DRYSCN Drying Oven with Natural Air Circulation LED



Natural Air
Convection



Max. temp.
300°C

Download
Catalogue



LED

Digital PID Controller

The DRYSCN universal drying oven is a precision device in your laboratory for heating, drying, ageing, sample preparation in science industry, quality assurance, education... Precision temperature sensor, programmable thermo controller, interior and exterior made of high quality materials, will give your work precision and comfort. Natural air circulation or forced air circulation provide high temperature uniformity in chamber and protect your samples. Corrosion resistant material is ideal for easy cleaning and long term exploitation, short heat up time save your time during the work process. High quality insulation prevents heat loss and saves your energy.



RT+5 -300°C

Up to 300°C hi temperature uniformity



Natural Air Convection

Natural Air Circulation – High Chamber Temperature Uniformity,



Microprocessor PID Control

Intelligent temperature controller with temperature and timing function prevent temperature hysteresis, overheating provide temperature stability...



Double Tempered Glass Window

for samples observation,



Time Programing

Timer programing from starting controler or when temperature reach setting value

	DRYSCN43	DRYSCN71	DRYSN136	DRYSCN225
Price				

Item	DRYSCN43	DRYSCN71	DRYSCN136	DRYSCN225
Volume Litter	43	71	136	225
Air Circulation	DRYSC Horizontal Forced Air Circulation/DRYSCN Natural air circulation			
Temperature range	Rt+5 - 300°C			
Temperature resolution	0,1°C			
Temperature fluctuation	1°C			
Display type	LED			
Temperature control mode	Two temperature section PID intelligent, sensor deviation correction, auto tuning,			
Adjustable exhaust air flap	Ø28mm on top with function of test hole			
Timer	0-9999min with timing wait function			
Housing	Cold rolling still with electro static spraying exterior with microbiological coating			
Temperature sensor	Pt100 A class			
Door with tempered glass for sample observation window	Yes, Dimension tempered glass H*W 250*204 mm			
Operation function	Temperature settings, timing function, auto stop, internal parameter locking, temperature correction, PID auto tuning, parameter memory in the case of electrical cut off, over temperature sound and light alarm, settings menu lock,			
Standard shelf number	2			
Optional shelf number (max)	9	13	17	21
Load per shelf (max)	15kg			
Voltage	220V/50-60Hz			
Power	1,2kW	1,6kW	2,3kW	3kW
Inner chamber size W*D*H mm	350*350*350	450*350*450	550*450*550	600*550*750
Outer Dimension W*D*H mm	652*472*587	750*470*680	852*572*786	902*622*986
NV/GV kg	33/37	45/50	62/68	77/96
Standard Temperature Certificate	At 160°C in the chamber centre Issued by COLO technical service			
Temperature certificate (optional)	One or multi point temp, mapping, issued by accredited laboratory			
Optional accessories	Shelf, Wi-Fi temperature control, Smart Phone			

Please note

If this Drying Oven does not match the specific needs of your application, or some options are not listed for sale, please feel free to contact us. Our manufacturing engineers will come up with technical solutions to meet your needs. We reserve the right to change technical specifications at any time.

COLO LabExperts



Laboratory Equipment production and Distribution

www.colo.si

Presernov Trg 9

8000 Novo Mesto

Slovenia

tel. +386 590 48 880 E-mail: office@colo.si

www.colo.si

© 2021 COLO Distributors Price List V1